

---

# **fake-useragent Documentation**

*Release master*

**hellysmile**

**Oct 04, 2018**



---

# Contents

---

<b>1</b>	<b>Features</b>	<b>3</b>
1.1	Installation . . . . .	3
1.2	Usage . . . . .	3
1.3	Notes . . . . .	4
1.4	Experiencing issues???	5
1.5	Tests . . . . .	6
1.6	Changelog . . . . .	6
1.7	Authors . . . . .	7



**info** Up to date simple useragent faker with real world database



- grabs up to date useragent from useragentstring.com
- randomize with real world statistic via w3schools.com

## 1.1 Installation

```
pip install fake-useragent
```

## 1.2 Usage

```
from fake_useragent import UserAgent
ua = UserAgent()

ua.ie
# Mozilla/5.0 (Windows; U; MSIE 9.0; Windows NT 9.0; en-US);
ua.msie
# Mozilla/5.0 (compatible; MSIE 10.0; Macintosh; Intel Mac OS X 10_7_3; Trident/6.0)'
ua['Internet Explorer']
# Mozilla/5.0 (compatible; MSIE 8.0; Windows NT 6.1; Trident/4.0; GTB7.4; InfoPath.2;
↳SV1; .NET CLR 3.3.69573; WOW64; en-US)
ua.opera
# Opera/9.80 (X11; Linux i686; U; ru) Presto/2.8.131 Version/11.11
ua.chrome
# Mozilla/5.0 (Windows NT 6.1) AppleWebKit/537.2 (KHTML, like Gecko) Chrome/22.0.1216.
↳0 Safari/537.2'
ua.google
# Mozilla/5.0 (Macintosh; Intel Mac OS X 10_7_4) AppleWebKit/537.13 (KHTML, like
↳Gecko) Chrome/24.0.1290.1 Safari/537.13
ua['google chrome']
```

(continues on next page)

(continued from previous page)

```
# Mozilla/5.0 (X11; CrOS i686 2268.111.0) AppleWebKit/536.11 (KHTML, like Gecko)
↳Chrome/20.0.1132.57 Safari/536.11
ua.firefox
# Mozilla/5.0 (Windows NT 6.2; Win64; x64; rv:16.0.1) Gecko/20121011 Firefox/16.0.1
ua.ff
# Mozilla/5.0 (X11; Ubuntu; Linux i686; rv:15.0) Gecko/20100101 Firefox/15.0.1
ua.safari
# Mozilla/5.0 (iPad; CPU OS 6_0 like Mac OS X) AppleWebKit/536.26 (KHTML, like Gecko)
↳Version/6.0 Mobile/10A5355d Safari/8536.25

# and the best one, random via real world browser usage statistic
ua.random
```

## 1.3 Notes

fake-useragent store collected data at your os temp dir, like /tmp

If You want to update saved database just:

```
from fake_useragent import UserAgent
ua = UserAgent ()
ua.update ()
```

If You don't want cache database or no writable file system:

```
from fake_useragent import UserAgent
ua = UserAgent (cache=False)
```

Sometimes, [useragentstring.com](http://useragentstring.com) or [w3schools.com](http://w3schools.com) changes their html, or down, in such case fake-useragent uses [heroku](http://heroku.com) fallback

If You don't want to use hosted cache server (version 0.1.5 added)

```
from fake_useragent import UserAgent
ua = UserAgent (use_cache_server=False)
```

In very rare case, if hosted cache server and sources will be unavailable fake-useragent wont be able to download data: (version 0.1.3 added)

```
from fake_useragent import UserAgent
ua = UserAgent ()

# Traceback (most recent call last):
# ...
# fake_useragent.errors.FakeUserAgentError

# You can catch it via

from fake_useragent import FakeUserAgentError

try:
    ua = UserAgent ()
except FakeUserAgentError:
    pass
```



If You will try to get unknown browser: (version 0.1.3 changed)

```
from fake_useragent import UserAgent
ua = UserAgent()
ua.best_browser
# Traceback (most recent call last):
# ...
# fake_useragent.errors.FakeUserAgentError
```

You can completely disable ANY annoying exception with adding fallback: (version 0.1.4 added)

```
import fake_useragent

ua = fake_useragent.UserAgent(fallback='Your favorite Browser')
# in case if something went wrong, one more time it is REALLY!!! rare case
ua.random == 'Your favorite Browser'
```

Want to control location of data file? (version 0.1.4 added)

```
import fake_useragent

# I am STRONGLY!!! recommend to use version suffix
location = '/home/user/fake_useragent%s.json' % fake_useragent.VERSION

ua = fake_useragent.UserAgent(path=location)
ua.random
```

If you need to safe some attributes from overriding them in UserAgent by `__getattr__` method use `safe_attrs` you can pass there attributes names. At least this will prevent you from raising FakeUserAgentError when attribute not found.

For example, when using fake\_useragent with `injections` you need to:

```
import fake_useragent

ua = fake_useragent.UserAgent(safe_attrs=('__injections__',))
```

Please, do not use if you don't understand why you need this. This is magic for rarely extreme case.

## 1.4 Experiencing issues???

Make sure that You using latest version!!!

```
pip install -U fake-useragent
```

Check version via python console: (version 0.1.4 added)

```
import fake_useragent

print(fake_useragent.VERSION)
```

And You are always welcome to post [issues](#)

Please do not forget mention version that You are using

## 1.5 Tests

```
pip install tox
tox
```

## 1.6 Changelog

- **0.1.11 October 4, 2018**
  - moved `s3` + `cloudfront` fallback to `heroku.com`, cuz someone from Florida did ~25M requests last month
- **0.1.10 February 11, 2018**
  - Minor fix docs `cloudfront` url
- **0.1.9 February 11, 2018**
  - fix `w3schools.com` renamed `IE/Edge` to `Edge/IE`
  - moved `heroku.com` fallback to `s3` + `cloudfront`
  - stop testing Python3.3 and pypy
- **0.1.8 November 2, 2017**
  - fix `useragentstring.com` Can't connect to local MySQL server through socket
- **0.1.7 April 2, 2017**
  - fix broken README.rst
- **0.1.6 April 2, 2017**
  - fixes bug `use_cache_server` do not affected anything
  - `w3schools.com` moved to https
  - `verify_ssl` options added, by default it is True (`urllib.urlopen` ssl context for Python 2.7.9- and 3.4.3- is not supported)
- **0.1.5 February 28, 2017**
  - added `ua.edge` alias to Internet Explorer
  - `w3schools.com` starts displaying Edge statistic
  - Python 2.6 is not tested anymore
  - `use_cache_server` option added
  - Increased `fake_useragent.settings.HTTP_TIMEOUT` to 5 seconds
- **0.1.4 December 14, 2016**
  - Added custom data file location support
  - Added fallback browser support, in case of unavailable data sources
  - Added alias `fake_useragent.FakeUserAgent` for `fake_useragent.UserAgent`
  - Added alias `fake_useragent.UserAgentError` for `fake_useragent.FakeUserAgentError`

- Reduced `fake_useragent.settings.HTTP_TIMEOUT` to 3 seconds
- Started migration to new data file format
- Simplified a lot 4+ years out of date code
- Better thread/greenlet safety
- Added verbose logging
- Added `safe_attrs` for prevent overriding by `__getattr__`
- **0.1.3 November 24, 2016**
  - Added hosted data file, when remote services is unavailable
  - Raises `fake_useragent.errors.FakeUserAgentError` in case when there is not way to download data
  - Raises `fake_useragent.errors.FakeUserAgentError` instead of `None` in case of unknown browser
  - Added `gevent.sleep` support in `gevent` patched environment when trying to download data
- **X.X.X xxxxxxxx xx, xxxx**
  - xxxxx ?????

## 1.7 Authors

You can visit [authors page](#)